



Wiha Insulated Screwdrivers with SoftFinish® Cushion Grip Handle

Insulation Test Standards:

Insulation according to IEC 900,
ASTM F-1505-01, New VDE
0682/part 201, DIN 7437,
NFPA70E

Responds to OSHA's use
specification 29 CFR1910



Each tool individually tested to
10,000 volts and certified to
1000 Volt ac or 1500 Volt dc

SoftFinish® handle

solid molded core
with soft outer
cushion grip. 40%
more torque than
conventional handles

Insulation
molded directly
onto the blade for
permanent bonding

Blade
CVM tool steel, hardened
to average 58/60RC

1000V



page 105



1000Volt

SHOP



1000Volt

SHOP

320 Slotted Screwdriver, With Wiha-SoftFinish® Handle

Insulation According to ASTM F-1505-01, New VDE Specification
0682/part 201 and IEC 900, NFPA70E, **up to 1000 Volt.**

Individually Tested. Blade high alloy chrome-vanadium-molybdenum
steel, hardened, black finish. Insulation molded directly onto blade.

Wiha-SoftFinish® handle, multi-component, cushion grip.

Item	↕	↔	↔	↔	↔	↔	↔	↔	↔	↔
No.	mm	Inch	mm	Inch	mm	Inch	lbs.	pkg.	Each	
320 05	2.0	.078	60	3.0	164	6.5	.05	10	\$4.68	
320 10	2.5	.098	75	3.0	179	7.1	.06	10	\$4.72	
320 12	3.0	.118	100	4.0	204	8.0	.07	10	\$4.72	
320 15	3.5	.139	100	4.0	204	8.0	.07	10	\$5.06	
320 17	4.0	.157	100	4.0	211	8.3	.12	10	\$6.02	
320 23	4.5	.177	100	4.0	211	8.3	.12	10	\$6.06	
320 24	4.5	.177	125	5.0	236	9.3	.12	10	\$6.06	
320 27	4.5	.177	150	6.0	261	10.2	.14	10	\$6.66	
320 25	4.5	.177	175	7.0	286	11.2	.13	10	\$6.80	
320 28	4.5	.177	200	8.0	311	12.3	.15	10	\$6.80	
320 31	5.5	.216	125	5.0	243	9.5	.15	10	\$6.84	
320 26	5.5	.216	175	7.0	293	11.5	.21	10	\$6.84	
320 34	6.0	.236	150	6.0	268	10.6	.21	10	\$8.38	
320 39	6.5	.255	150	6.0	268	10.6	.21	10	\$8.40	
320 42	8.0	.315	175	7.0	299	11.8	.34	10	\$10.80	
320 45	10.0	.393	200	8.0	318	12.5	.39	10	\$13.90	

Warning!

Insulated tools are not intended for use on live or energized circuits. Always
disconnect and de-energize all equipment & circuits. **NEVER!** work on live
or energized circuits or equipment.

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation

Inspect insulation prior to each use of any insulated tool

If you doubt the integrity of the insulation destroy the tool or have it retested

Use insulated tools where the ambient temperature is between -20 to +70° C

Have a qualified safety technician inspect and re-certify tools annually for safe use

321 Phillips Screwdriver, With Wiha-SoftFinish® Handle

Insulation According to ASTM F-1505-01, New VDE Specification
0682/part 201 and IEC 900, NFPA70E, **up to 1000 Volt.**

Individually Tested. Blade high alloy chrome-vanadium-molybdenum
steel, hardened, black finish. Insulation molded directly onto blade.

Wiha-SoftFinish® handle, multi-component, cushion grip.

Item	↕	↔	↔	↔	↔	↔	↔	↔	↔	↔
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.	Each		
321 00	0	60	2.4	164	6.5	.06	10	\$5.06		
321 01	1	80	3.0	191	7.5	.12	10	\$5.88		
321 02	2	100	4.0	218	8.6	.20	10	\$7.42		
321 03	3	150	6.0	268	10.6	.34	10	\$10.56		
321 04	4	200	8.0	318	12.5	.39	10	\$12.16		



1000Volt

SHOP

320 90 Set 4 Pcs. Slotted & Phillips

Item	↕	↔	↔	↔	↔	↔	↔	↔	↔	↔
No.	mm	mm	mm	Size	mm					
320 90	320 15	3.5	100	0.6	321 01	1	80	Each		
	320 24	4.5	125	1.0	321 02	2	100	\$24.42		